


Technical Data



LooseLay

	Standard	Result
Description		Decorative Vinyl Woodplanks and Tiles
Thickness		4.5mm
Wear layer		0.5mm
Backing		PVC Friction Pad
Guarantee		Residential Limited Lifetime Wear* Commercial 10-Years Wear*
K-Guard Plus		Yes
Bevelled edge		No
Box quantity		12 Planks / 3.15m ² 10 Tiles / 3.05m ²
Standards	EN 649 & ASTM - 1700	
Classification	EN 685:33 ASTM F-1700	Commercial Heavy Duty Domestic Heavy Duty
Reaction to fire	AS/ISO 9239.1:2003 Radiant Panel Test	CRF: Plank 8.0 kW/m ² Smoke value: 105% min Tile 9.4 kW/m ² 164% min
Slip resistance	AS/NZS 4586:1999	
Staining/Chemical resistance	EN 423 ASTM F-925	Class 0 Pass
Light fastness	ISO 105-B02 ASTM F-1515	≥ 7 < 8
Abrasion resistance	EN 660-2 ASTM 3884	Group T Pass
Dimensional stability	EN 434 ASTM F2199-02	<0.25% <0.05%
Acoustic properties	ISO 140-6 Normalized Impact Sound Insulation ISO 140-8 Improved Impact Sound Insulation ASTM E492-09 Impact Insulation Class	L' n, w (C1) 59dB ΔL, w 14dB IIC 56dB Suitable for use on upper floors of residential high-rise apartment buildings without the need for a separate acoustic underlay
Electrical behaviour - body voltage	EN 1815 AATCC 134-1996	Pass Pass
Residual indentation	EN 433 ASTM F-1914	<0.1mm <0.003 in
Castor chair continuous use	EN 425 ASTM D-3884	Pass Pass
Thermal conductivity	ISO 8302	0.0245m ² K/W
Suitable for underfloor heating		Yes
Exposure to water		Suitable in wet areas of the home - refer to the LooseLay Installation Guide under "Domestic Wet Areas"
Adhesive		Loose-laid over complete floor; unless very heavy traffic and/or strong sunlight expected, then perimeter and grid stick using Karndean Hi-Tack PS adhesive to box installation instructions
Recyclable		Yes

Product Code	Size	Oil-Wet Ramp	Wet Pendulum
VG5-7LLST	1050mm x 250mm (41.3" x 9.85")	R10	X
VGW33T-7LLST			
VGW38T-7LLST			
VGW39T-7LLST			
VGW9IT-7LLST			
VGW92T-7LLST	610mm x 500mm (24" x 19.7")	R9	Y
LLT200			
LLT201			
LLT202			
LLT203			



*Full details of the terms and conditions of the Karndean LooseLay residential limited and commercial wear guarantees are available by contacting Karndean International. Freecall: 1800 428 963 Fax: 1800 431 048 or Email: customerservice@karndean.com.au.

For more information:

Australia

Call: 1800 810 920

Email: customerservice@karndean.com.au

Visit: www.karndean.com.au

New Zealand

Call: 0800 44 21 01

Email: customerservice@karndean.co.nz

Visit: www.karndean.co.nz



Your space. Your needs. Your style.